

Yacht Braid Break Strains



	PBO ELITE	SUPERBRAID	CHALLENGE BRAID	SPECTRASPEED	YACHTMASTER XS	SOUTHERN LIGHTS	DINGHY RACING	DINGHY LINE	DOCKLINE	OCEAN12	SPECTRA SOLO	
diameter mm	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	average break load kgs	diameter mm
2				295								2
3			550	470						1500		3
4			700	735						2000		4
5			1200	1100		660				3100	1450	5
6	2700	2110	1630	1570	1195	1170	1270			4200		6
7		3110	2000								2800	7
8	4600	3670	3600	3200	1650	2110	2260	1595		6600		8
9		4460									4300	9
10	7100	6370	6800	4950	2890			2695	3400	11000		10
11											5800	11
12	10100	7660	8100	5985	4570			3520	5000	16500		12
14	12800	8800	10400	7600	4720			4620	7300	21200		14
16	17200	10750	11900	9400	5530				8000	27300		16
18	23000	12400	14200	10350	6330				8670			18
20		15200	16400	12000	7240				10700			20
22		18700	20200	14800	8600				12860			22
24		20700	23200	18400	9800				15200			24
26		23100	25600	20400					17800			26
28		25900	28400	21900					20600			28
30		29800	32300	23500					23600			30

Note: Above break loads are approximate only, test certificates can be supplied with product. Most products are covered with standard polyester covers, Special cover systems are available on all products.